


| REV. | ECN NO. | DATE |
|------|----------|----------|
| 1.0 | RELEASED | 07/28/02 |
| 1.1 | REVISED | 10/17/02 |

SPECIFICATIONS

CURRENT RATING : 1 AMPS
 INSULATOR RESISTANCE : 5000 MEGOHMS MIN.
 CONTACT RESISTANCE : 20 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING : AC 500V
 OPERATING TEMPERATURE : -40°C - +105°C
 MAX PROCESSING TEMP. : 230°C FOR 30 ~ 60 SECONDS
 (260°C FOR 10 SECONDS)
 CONTACT MATERIAL : PHOSPHOR BRONZE
 INSULATOR MATERIAL : POLYESTER, UL 94V-0
 STANDARD : NYLON-6T
 CONTACT PLATED : FULL GOLD, FULL TIN, SELECTIVE PLATED

| | | | | |
|---------------------------------|-------------------|------------|--|--|
| 比例 (SCALE) | 4:1 | 繪圖 (DRAW) | ZHAONENGMEI |  GTK UK LTD. |
| 單位 (UNIT) | MM | 審核 (CHECK) | / / | |
| 一般公差 (TOLERANCE) | 承認 (AP'E) | / / | 圖名 (NAME) : FEMALE HEADER P2.0mm PROFILE : 4.4mm, SMT 2*XXP | |
| .0=±0.35 .00=±0.2 ANG=±5° | 投影法 PROJECTION | 第三角 | 料號 (PART NO) FHDSXXG3 | |
| | | | 圖號 (DRAW NO) 20021017-01(F219A) | |