



NOTES:

1. MATERIAL:
PBT glass-filled, UL94V-0 (halogen free)
Natural colour
2. PACKAGING:
1000pcs/Bag
3. ORDER CODE:
WB1J-xxS-CF3K-R

#poles; 02-15
4. USE WITH:
Crimp contact p/n WB1J-CR-FTR-R

Poles	A	B	C	D
02	1.25	3.75	2.35	-
03	2.50	5.00	3.20	
04	3.75	6.25	4.25	
05	5.00	7.50	6.25	8.75
06	6.25	8.75		
07	7.50	10.00		
08	8.75	11.25	8.20	10.70
09	10.00	12.50		
10	11.25	13.75		
11	12.50	15.00	17.50	18.75
12	13.75	16.25		
13	15.00	17.50		
14	16.25	18.75	20.00	
15	17.50	20.00		

X. ± 0.40	X.* ± 5.0*	UNITS: mm	NAME(INTENDED USE):	GTK UK LTD.
.X ± 0.30	.X* ± 2.0*	MATERIAL:	CUSTOMER	
.XX ± 0.20	.XX* ± 1.0*	SEE NOTE	PART NO.(INTENDED USE):	TITLE:
.XXX ± 0.10	.XXX* ± ---	FINISH:	WB1J-xxS-CF3K-R	1.25mm Pitch/Disconnectable Crimp Style Connectors
<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF CHYAO SHIUNN ELECTRONIC CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF CHYAO SHIUNN ELECTRONIC CO., LTD.</small>			APPD:	DWG NO.:
			CHKD:	020-0144-1288S-XX
			DR:	SCALE SHEET REV.
			sunquan 2012/07/13	5:1 1/1 /

ROHS COMPLIANT

