



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 4. BERYLLIUM COPPER PER QQ-C-530

RoHS COMPLIANT

						DIMENSIONS ARE IN MILLIMETERS			PART NO.	
						UNLESS OTHERWISE SPECIFIED TOLERANCES (一般公差) 0.5~6 = ±0.2 >6~30 = ±0.4 >30~120 = ±0.6 >120~315 = ±1 >315~1000 = ±1.6 ANGLES(角度) = ±5°			APPROVED	DATE
INSULATOR	PTFE	WHITE			<i>Jany</i>				02/25/13'	
BODY	NOTE 1	NOTE 2			CHECKED				DATE	
INSULATOR	PTFE	WHITE			<i>Jany</i>				02/25/13'	
CONTACT PIN	NOTE 4	NOTE 3			DRAWN	DATE	TITLE	MCX R/A PCB MOUNT JACK		
CUBE BODY	NOTE 1	NOTE 2			<i>Adina</i>	02/25/13'	DRAWING NO.	MCX-J1T-GG25-R		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	6/1	ISSUE	A2	

