


- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  4. TEFLON MIL-P-19468
  5. BERYLLIUM COPPER PER QQ-C-530

RoHS COMPLIANT

					DIMENSIONS ARE IN MILLIMETERS				PART NO.		 <b>GTK UK LTD.</b>	
					UNLESS OTHERWISE SPECIFIED TOLERANCES (-公差)				APPROVED	DATE		
					0.5~6	= ±0.2				<i>[Signature]</i>	11/25/10'	MMCX PCB MOUNT JACK
					>6~30	= ±0.4				<i>[Signature]</i>	11/25/10'	DRAWING NO. MMCX-J2T-GG25-R
					>30~120	= ±0.6						
					>120~315	= ±1						
					>315~1000	= ±1.6						
					ANGLES(角度) = ±5'							
CONTACT PIN	NOTE 5	NOTE 3										
INSULATOR	NOTE 4	WHITE										
BODY	NOTE 1	NOTE 2										
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	10/1	ISSUE	A2	<i>[Signature]</i>	11/25/10'	