


P.C.B. LAYOUT

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
4. TEFLON MIL-P-1946B
5. BERYLLIUM COPPER PER QQ-C-530
6. GOLD PL 3 MIN OVER ELECTROLESS NICKEL PL 120 MIN THICK OVER COPPER PL 60 MIN THICK

RoHS COMPLIANT

					DIMENSIONS ARE IN MILLIMETERS				PART NO.		 <b>GTK UK LTD.</b>	
					UNLESS OTHERWISE SPECIFIED TOLERANCES (-公差)				APPROVED	DATE		
					0.5~6 = ±0.2				<i>Jay</i>	08/22/11'		
C RING	NOTE 5	NOTE 6			>6~30 = ±0.4				CHECKED	DATE		MMCX PCB MOUNT PLUG
CONTACT PIN	NOTE 1	NOTE 3			>30~120 = ±0.6				<i>Anel</i>	08/22/11'		
INSULATOR	NOTE 4	WHITE			>120~315 = ±1				DRAWN	DATE		DRAWING NO.
BODY	NOTE 1	NOTE 2			>315~1000 = ±1.6				<i>Polly</i>	08/22/11'		MMCX-M2T-GG25-R
NO.	DESCRIPTION	MATERIAL	FINISH	QTY	DRAWING NO.	SCALE	8/1	ISSUE	A2			