

PCB LAYOUT/TOP VIEW

RoHS COMPLIANT



MATERIALS:

PLASTIC HOUSING: ENGINEERING THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0.
 COLOUR :BLACK.

PLASTIC INSERT: ENGINEERING THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0.
 PANTONE COLOUR NO. :COOL GRAY 5U(GRAY)

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT, 3µ"
 TIN PLATING OVER NICKEL IN SOLDER AREA.

設計 DR. Kathy Chung 2011/03/28	核准 APPD. Jerry 2011/03/28	容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	TOLERANCE	品名 ARTICLE 6P OUTSIDE 4P4C PCB JACK
版本說明 REVISION NOTE 更正 12.85 公差為 +0/-0.20, 圖面發 A 版。				圖號 DWG NO. MTC-4410NBMU-R
 GTK UK LTD.				單位 UNIT mm
				比例 SCALE 張數 SHEET 版本 REV. 3/1 1/1 A