


Electrical Characteristics :

- Insulation Resistance : 100MΩ Min.
- Contact Resistance : 50mΩ Max.
- Withstand Voltage : 500 VAC 1 minute.
- Current Rating : 1.0A

Material:

- Housing : High-Thermoplastic UL94V-0
- Contact : Selective Gold Plating
- Terminal: 0.3mm Thickness Copper Alloy, Tin Plated on the Solder Area.
- Shield : Alloy, Nickel Plating.



Recommended Panel Cut-out



| | | | | | | | | | | | | | |
|----------|-----------------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------|-------|-------|-----------|--------|-------|--------|-----------|------|-------------|-----------|
| TITLE | RJ45, SHIELDED, RECEPTACLE, HORIZONTAL, SINGLE PORT, THT (RoHS) | | OPEN TOLERANCES Fraction Decimals Angles X ±0.50 ± 1° XX ±0.38 XXX ±0.25 XXXX ±0.10 | DWG. | Kate | 07/18/16' | | | | | | | |
| PART NO. | MTC-881ESN-R | REV. | A | SCALE | 2 : 1 | SHEET | 1 of 1 | APPD. | Justin | 07/18/16' | | | |
| REF. NO. | | QA. NO. | | | | | | | | | A | New Release | 07/18/16' |
| | | | | | | | | | | | REV. | DESCRIPTION | DATE |