


NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
4. TEFLON MIL-P-19468
5. BRASS JIS H 3250,C 3601

RoHS COMPLIANT

					DIMENSIONS ARE IN MILLIMETERS			PART NO.		 GTK UK LTD.		
					UNLESS OTHERWISE SPECIFIED TOLERANCES (-公差)			APPROVED	DATE			TITLE
INSULATOR	NOTE 4	WHITE			0.5~6 = ±0.2			<i>Jan</i>	12/14/11	SMB R/A PCB MOUNT JACK		
INSULATOR	NOTE 4	WHITE			>6~30 = ±0.4							
BODY	NOTE 1	NOTE 2			>30~120 = ±0.6			CHECKED	DATE			
CONTACT PIN	NOTE 5	NOTE 3			>120~315 = ±1			<i>Anel</i>	12/14/11			
CUBE BODY	NOTE 1	NOTE 2			>315~1000 = ±1.6			DRAWN	DATE	DRAWING NO.		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A3	<i>Polly</i>	12/14/11	SMB-J1T-GG25-R