



■ SPECIFICATIONS

- Current Rating : 1.0 A AC/DC
- Withstanding Voltage : 250V AC/minute
- Insulation Resistance : 100M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max

■ HOUSING

- Part No. : WBPM-xxS-CF3-R
- Poles : 02~30
- Material :
 1. 02P~20P: Nylon 66 UL94V-0
 2. 22P~30P : PBT UL94V-0 ▲

Poles	Dimensions (mm)		
	A	B	C
2	1.25	2.70	----
3	2.50	3.95	----
4	3.75	5.20	2.50
5	5.00	6.45	3.75
6	6.25	7.70	5.00
7	7.50	8.95	6.25
8	8.75	10.20	7.50
9	10.00	11.45	8.75
10	11.25	12.70	10.00
11	12.50	13.95	11.25
12	13.75	15.20	12.50
13	15.00	16.45	13.75
14	16.25	17.70	15.00
15	17.50	18.95	16.25
16	18.75	20.20	17.50
18	21.25	22.70	20.00
20	23.75	25.20	22.50
22	26.25	27.70	22.50
24	28.75	30.20	22.50
26	31.25	32.70	22.50
28	33.75	35.20	22.50
30	36.25	37.70	22.50



GTK UK LTD

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	▲	變更原因遺失	余秀麗	2005/05/15	▲			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	▲	產品與圖面不符	曲智浩	2005/07/20	▲			
黃科源	⊕	a4	.000 ±0.10	▲	增加視圖	黃科源	2009/03/19	▲			
DRAWN BY	DATE	SIZE	ANGLE		變更產品材料	王誠賢	2011/12/19		CUSTOMER		
王誠賢	2011/12/19	A4	0° ±1°	▲					Conforms to The RoHS Instruction		
			.0° ±	▲							
			SHEET	1/1	▲						

PART NO WBPM-xxS-CF3-R
1.25mm Wire to Board Connector