


3 Circuit



2 Circuit

■ SPECIFICATIONS

- Voltage Rating : 125V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 250V AC /minute
- Insulation Resistance : 100MΩ min
- Temperature Range : - 40°C to + 85°C
- Contact Resistance : 20mΩ max

■ WAFER

- Part No. : WTBB-xxS-TH2T-R
- Poles : 2 - 15(DIP Type)
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-0
- Q' ty : 1,000 Pcs./PVC Box

Poles	Dimensions (mm)		
	A	B	C
2	1.25	4.25	3.05
3	2.50	5.50	4.30
4	3.75	6.75	5.55
5	5.00	8.00	6.80
6	6.25	9.25	8.05
7	7.50	10.50	9.30
8	8.75	11.75	10.55
9	10.00	13.00	11.80
10	11.25	14.25	13.05
11	12.50	15.50	14.30
12	13.75	16.75	15.55
13	15.00	18.00	16.80
14	16.25	19.25	18.05
15	17.50	20.50	19.30



APPROVED BY	林宗	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
				.0	±0.3						
CHECKED BY	PROJ	DRAWN BY	DATE	VER NO.		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
				.000	±0.1						
PART NO.	WTBB-xxS-TH2T-R	DRAWN BY	DATE	SIZE		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
				ALL	±						
1.25mm wire-to-board header, through hole, vertical	黄科源	DATE	2009/07/07	SIZE		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
				0°	±						
								CUSTOMER			
										Conforms to The RoHS Instruction	