



■ SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩmin
- Temperature range: -25°C~+85°C
- Contact resistance: Initial Value/10mΩ max
After environmental testing/20mΩ max

■ HOUSING

- Part No.: WTBC-xxS-CF3T-R
- Poles: 2-12 └ No. of poles
- Material: Nylon 66 UL94V-0
- Q'ty: 1000pcs/bag

| Poles | Part No. | Dimension(mm) | | Poles | Part No. | Dimension(mm) | |
|-------|------------|---------------|------|-------|------------|---------------|------|
| | | A | B | | | A | B |
| 2 | JS-1121-02 | 3.96 | 7.9 | 7 | JS-1121-07 | 23.75 | 27.9 |
| 3 | JS-1121-03 | 7.92 | 11.9 | 8 | JS-1121-08 | 27.72 | 31.9 |
| 4 | JS-1121-04 | 11.88 | 15.9 | 9 | JS-1121-09 | 31.68 | 35.9 |
| 5 | JS-1121-05 | 15.84 | 19.9 | 10 | JS-1121-10 | 35.64 | 39.9 |
| 6 | JS-1121-06 | 19.80 | 23.9 | 11 | JS-1121-11 | 39.60 | 43.9 |
| | | | | 12 | JS-1121-12 | 43.56 | 47.9 |

ROHS COMPLIANT

| DRAWN BY | DESIGNED BY | UNIT | SCALE | TOLERANCE |
|------------|-------------|----------|---------|-----------|
| | | mm | | ±0.25 |
| CHECKED BY | APPROVED BY | DATE | VER NO. | |
| | | 08-06-01 | A | |



GTK UK LTD.

PART NO.

WTBC-xxS-CF3T-R